



Laser Head

Nominal output frequency	473.61221 THz ± 25 MHz
Output power (all SL models)	> 1 mW
Beam output	FC/APC-collimator, single mode fiber
Warm-up time	< 10 min
Frequency stability (after 1 min / 1 h / 1 d)	$\pm 2 \times 10^{-9} / \pm 5 \times 10^{-9} / \pm 1 \times 10^{-8}$
Operating temperature	+ 15 °C to + 30 °C
Storage temperature	- 20 °C to + 50 °C
Laser head dimensions [Ø × L]	Ø 50 x 410 mm
Length, connection cord (laser/power supply)	1.5 m
Weight	900 g
Laser safety class	3R
High Altitude Option	available

Power Supply

Input voltage	95 – 265 V
Line plug availability	Europe, USA/Japan, Australia
Weight	350 g

Testing and Certifications

EMC	EN 50081-1	3/93
	EN 50082-2	2/96
Safety	EN 60950	9/94
Certifications	VDE, UL, JETL (others e.g. VDE-ENEC have been applied for)	
CE-symbol in compliance with	EU guidelines 73/23/EWG and 89/336/EWG Unified EN-standards EN 61010-1, EN 60825-1, EN 55011, and 50082-1	



Calibration Source

SL02



HighFinesse

The Standard of Accuracy

Further Information

For further technical information, application examples, diagrams and for customisation of calibration sources please contact:

HighFinesse Team

service@highfinesse.de



HighFinesse GmbH
Wöhrdstraße 4
72072 Tübingen, Germany



T +49 (0) 7071 - 53918 0
F +49 (0) 7071 - 5391899
M info@highfinesse.com



Additional information
and distributors:
www.highfinesse.com