



## Laser Head

Nominal output wavelength	473.61221 THz $\pm$ 5 MHz
Output power (all SL models)	> 0.8 mW
Beam output	FC/APC-collimator, single mode fiber
Warm-up time	ca. 10 min
Frequency stability (after 1 min / 1 h / 1 d)	$\pm 1 \times 10^{-9}$ / $\pm 2 \times 10^{-9}$ / $\pm 5 \times 10^{-9}$
Operating temperature	+ 15 C° to + 30 C°
Storage temperature	- 20 C° to + 50 C°
Laser head dimensions [ $\varnothing \times L$ ]	$\varnothing$ 34.9 x 280 mm
Length, connection cord (laser/power supply)	0.8 m
Weight	450 g
Laser safety class	2M
High Altitude Option	available

## Power Supply

Input voltage	100 – 240 V
Line plug availability	Europe, USA/Japan, Australia
Weight	1200 g
Dimensions	172 x 60 x 230 mm

## Testing and Certifications

EMC	EN 50081-1	3/93
	EN 50082-2	2/96
Safety	EN 60950	9/94
Certifications	VDE, UL, JETL (others e.g. VDE-ENEC have been applied for)	
CE-symbol in compliance with	EU guidelines 73/23/EWG and 89/336/EWG Unified EN-standards EN 61010-1, EN 60825-1, EN 55011, and 50082-1	



Calibration Source

SL03



HighFinesse  
Laser and Electronic Systems

## Options

Optical Isolator (i)

The system can be equipped with an optical faraday isolator to minimize optical feedback and increase the stability of the laser system

## Recommended Wavelength Meter

WS7-30, WS7-30 UV-I, WS7-30 IR-I

WS7-60 IR-I

Older models:

WSU30, WSU30 UV-I, WSU30 IR-I

## Further Information

For further technical information, application examples, diagrams and for customisation of calibration sources please contact:

Mathias Bories

[service@highfinesse.de](mailto:service@highfinesse.de)



HighFinesse GmbH  
Wöhrdstraße 4  
72072 Tübingen, Germany



T +49 (0) 7071 - 53918 0  
F +49 (0) 7071 - 5391899  
M [info@highfinesse.com](mailto:info@highfinesse.com)



Additional information  
and distributors:  
[www.highfinesse.com](http://www.highfinesse.com)