

Laser Head


Nominal output frequency	473.61221 THz ± 5 MHz
Output power (all SL models)	> 0.8 mW
Beam output	FC/APC-collimator, single mode fiber
Warm-up time	ca. 10 min
Frequency stability (after 1 min / 1 h / 1 d)	$\pm 1 \times 10^{-9}$ / $\pm 2 \times 10^{-9}$ / $\pm 5 \times 10^{-9}$
Operating temperature	+ 15 °C to + 30 °C
Storage temperature	- 20 °C to + 50 °C
Laser head dimensions [Ø × L]	Ø 34.9 x 280 mm
Length, connection cord (laser/power supply)	0.8 m
Weight	450 g
Laser safety class	2M
High Altitude Option	available

Power Supply

Input voltage	100 – 240 V
Line plug availability	Europe, USA/Japan, Australia
Weight	1200 g
Dimensions	172 × 60 × 230 mm

Testing and Certifications

EMC	EN 50081-1	3/93
	EN 50082-2	2/96
Safety	EN 60950	9/94
Certifications	VDE, UL, JETL (others e.g. VDE-ENEC have been applied for)	
CE-symbol in compliance with	EU guidelines 73/23/EWG and 89/336/EWG Unified EN-standards EN 61010-1, EN 60825-1, EN 55011, and 50082-1	



Calibration Source

SL04



HighFinesse
Laser and Electronic Systems

Options

Optical Isolator (i)

The system can be equipped with an optical faraday isolator to minimize optical feedback and increase the stability of the laser system

Recommended Wavelength Meter

WS7-30, WS7-30 UV-I, WS7-30 IR-I

WS7-60 IR-I

Older models:

WSU30, WSU30 UV-I, WSU30 IR-I

Further Information

For further technical information, application examples, diagrams and for customisation of calibration sources please contact:

Mathias Bories

service@highfinesse.de



HighFinesse GmbH
Wöhrdstraße 4
72072 Tübingen, Germany



T +49 (0) 7071 - 53918 0
F +49 (0) 7071 - 5391899
M info@highfinesse.com



Additional information
and distributors:
www.highfinesse.com