

# Linewidth Analyzer LWA-10k VIS



HighFinesse  
The Standard of Accuracy

## Analyzer Unit


Input	min.	max.	typ.
Wavelength range <sup>1)</sup>	450 nm	1064 nm	780 nm
Input power range	0.5 mW	8 mW	5 mW
Input power stability	±5 %		
Laser type	CW, single-mode		
Input type	FC/APC		
Scan stroke (@ fscan > 10 Hz)	—	40 MHz	

### Sample Frequency Noise Specification for Different Frequency Ranges <sup>2)</sup>

	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	> 1 MHz
Noise floor (Hz/√Hz)	500	150	60	60	50	30
Frequency noise density range (Hz/√Hz)	30 – 10 M					
Minimum intrinsic linewidth (Lorentzian linewidth)	< 12 kHz					
Effective linewidth range (β-separation)	< 20 kHz – 30 MHz					
Dynamic range	60 dB					

1) For customized wavelength ranges please contact: [service@highfinesse.de](mailto:service@highfinesse.de)

2) Specified for 5 mW input power at a wavelength of 1550 nm.



# Linewidth Analyzer LWA-10k VIS



HighFinesse  
The Standard of Accuracy

---

## Analyzer Unit

---

### Lineshape Specification

---

Effective linewidth range (optical linewidth) [curve fitting method]	< 20 kHz – 10 MHz
Dynamic range	60 dB
Frequency noise bandwidth	10 Hz – 10 MHz

---

### Miscellaneous

---

Interface	Ethernet
Analog output	$\pm 7.5\text{V}$ (50 $\Omega$ )
Dimensions	440 × 340 × 155 mm
Weight	12.0 kg


---

## Digitizer Module

---

Sample rate (Sa/s)	62.5 M
Resolution	16 bits
Acquisition time	1 ms – 100 ms
Evaluation time	10 ms – 1 s
Interface	USB 3.0 type B
Dimensions	210 × 200 × 74 mm
Weight	2.0 kg

---



Linewidth Analyzer  
LWA-10k VIS



HighFinesse  
The Standard of Accuracy

---

## Software

---

Operating system	Microsoft® Windows® 10, 64 Bit
CPU (minimum)	Intel® Core™ i5 or equivalent
Memory (minimum)	8 GB
Graphical evaluation options	Frequency noise density spectrum, lineshape spectrum, intrinsic (Lorentzian) linewidth, effective (optical) linewidth

---

## Further Information

For further technical information, application examples, diagrams  
and for customisation of linewidth analyzers please contact:

HighFinesse Service

[service@highfinesse.de](mailto:service@highfinesse.de)



HighFinesse GmbH  
Wöhrdstraße 4  
72072 Tübingen, Germany



T +49 (0) 7071 - 53918 0  
F +49 (0) 7071 - 53918 99  
M [info@highfinesse.com](mailto:info@highfinesse.com)



Additional information  
and distributors:  
[www.highfinesse.com](http://www.highfinesse.com)