



Switches

Photonic Crystal Switch



HighFinesse

The Standard of Accuracy

Measurement Range

370 – 2000 nm

The wavelength range of the wavemeter will limit the measurement

Technical Specs

Available channels	2, 4, 8
Guaranteed transmission	15 % @ 633 nm
Return loss	< 40 dB
Crosstalk	< -55 dB
Switching time	typ. 12 ms
Supply voltage	5 V
Power consumption	450 mW
Operating temperature	0 – 60° C
Storage temperature	-40° – 80° C
Operating Relative Humidity	35 – 55 %
Housing dimensions, 2 channels	125 mm × 200 mm (+fiber) × 43 mm
Housing dimensions, 4 channels	165 mm × 242 mm (+fiber) × 43 mm
Housing dimensions , 8 channels	222 mm × 200 mm (+fiber) × 43 mm
Standard interface	TTL
Optional interface	USB, RS232

Further Information

For further technical information, application examples, diagrams and for customisation of photonic crystal switches please contact:

HighFinesse Service

service@highfinesse.de



HighFinesse GmbH
Wöhrdstraße 4
72072 Tübingen, Germany



T +49 (0) 7071 - 53918 0
F +49 (0) 7071 - 5391899
M info@highfinesse.com



Additional information
and distributors:
www.highfinesse.com