

Switches

Single Mode



HighFinesse


The Standard of Accuracy

Available Measurement Ranges

SM 405	405 nm single mode, Wavelength range 370 – 650 nm
SM 630	630 nm single mode, Wavelength range 600 – 850 nm
SM 780	780 nm single mode, Wavelength range 750 – 1020 nm
SM 980	980 nm single mode, Wavelength range 950 – 1300 nm
SM 1300	1300 nm single mode, Wavelength range 1250 – 2000 nm

Technical Specs

Available channels:	2, 4, 8
Guaranteed transmission	20 %
Return loss	< 40 dB
Crosstalk	< -55 dB
Switching time	typ. 12 ms
Supply voltage	5 V
Power consumption	450 mW
Operating temperature	0 – 60° C
Storage temperature	-40° – 80° C
Operating Relative Humidity	35 – 55 %
Housing dimensions, 2 and 4 channels	175 × 110 × 48 mm
Housing dimensions, 8 channels	225 × 110 × 48 mm
Standard interface	TTL
Optional interface	USB, RS232



Switches

Single Mode



HighFinesse
The Standard of Accuracy

Further Information

For further technical information, application examples, diagrams
and for customisation of single mode switches please contact:

HighFinesse Service

service@highfinesse.de



HighFinesse GmbH
Neckarsulmer Straße 5
72072 Tübingen, Germany



T +49 (0) 7071 - 53 918 0
F +49 (0) 7071 - 53 918 99
M info@highfinesse.com



Additional information
and distributors:
www.highfinesse.com